

Please type a plus sign (+) inside this box → ☐

PTO/SB/05 (08)
Approved for use through 09/30/2000. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No. **9127-1E006US1**
First Inventor or Application Identifier **Robert S. Deland**
Title **MAGNETIC STRIPE AUTHENTICATION AND VERIFICATION SYSTEM**
Express Mail Label No. **EL236490496US**

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. ☒ * Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☒ Specification [Total Pages **34**]
(preferred arrangement set forth below)
 - Descriptive title of the Invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets **8**]
4. Oath or Declaration [Total Pages **2**]
 - a. ☒ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d))
(for continuation/divisional with Box 16 completed)
 - i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).

*** NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).**

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

5. ☐ Microfiche Computer Program (Appendix)
6. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

7. ☒ Assignment Papers (cover sheet & document(s))
8. ☒ 37 C.F.R. § 3.73(b) Statement (when there is an assignee) ☒ Power of Attorney
9. ☐ English Translation Document (if applicable)
10. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
11. ☐ Preliminary Amendment
12. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
13. ☒ * Small Entity Statement(s) ☐ Statement filed in prior application, Status still proper and desired (PTO/SB/09-12)
14. ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)
15. ☒ Other: **Check No. 1357 for \$459**

- 16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:**
- ☐ Continuation ☐ Divisional ☒ Continuation-in-part (CIP) of prior application No: **09 / 120,816**
- Prior application information: Examiner **not yet assigned** Group / Art Unit: **2876**

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label or ☒ Correspondence address below
(Insert Customer No. or Attach bar code label here)

Name	Byard G. Nilsson				
	Registration No. 17,350				
Address	DARBY & DARBY, P.C.				
	707 Wilshire Boulevard, 32nd Floor				
City	Los Angeles	State	California	Zip Code	90017
Country	U.S.A.	Telephone	(213) 243-8000	Fax	(213) 243-8050

Name (Print/Type)	Robert A. Green	Registration No. (Attorney/Agent)	28,301
Signature	<i>Robert A. Green</i>	Date	June 3, 1999

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

**STATEMENT CLAIMING SMALL ENTITY STATUS
(37 CFR 1.9(f) & 1.27(b))--INDEPENDENT INVENTOR**

Docket Number (Optional)
9127-0E390US0

Applicant, Patentee, or Identifier: Robert S. Deland

Application or Patent No.: _____

Filed or Issued: June 3, 1999

Title: MAGNETIC STRIPE AUTHENTICATION AND VERIFICATION SYSTEM

As a below named inventor, I hereby state that I qualify as an independent inventor as defined in 37 CFR 1.9(c) for purposes of paying reduced fees to the Patent and Trademark Office described in:

- ☒ the specification filed herewith with title as listed above.
☐ the application identified above.
☐ the patent identified above.

I have not assigned, granted, conveyed, or licensed, and am under no obligation under contract or law to assign, grant, convey, or license, any rights in the invention to any person who would not qualify as an independent inventor under 37 CFR 1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern, or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:

- ☐ No such person, concern, or organization exists.
☒ Each such person, concern, or organization is listed below.

MAG-TEK, INC.
20725 South Annalee Avenue
Carson, California 90746

Separate statements are required from each named person, concern, or organization having rights to the invention stating their status as small entities. (37 CFR 1.27)

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

Robert S. Deland

NAME OF INVENTOR

NAME OF INVENTOR

NAME OF INVENTOR

Robert S. Deland
Signature of inventor

Signature of inventor

Signature of inventor

May 25, 1999
Date

Date

Date

MAGNETIC STRIPE AUTHENTICATION AND VERIFICATION SYSTEM

5 This is a continuation-in-part of Application Serial No. 09/120,816 entitled MAGNETIC STRIPE CARD VERIFICATION SYSTEM filed July 22, 1998.

BACKGROUND AND SUMMARY OF THE INVENTION

10 Generally, the present development relates to systems and processes utilizing the repeatable characteristics of a magnetic stripe for authenticating stripe bearing objects, e.g., documents as credit cards.

15 Various forms of cards and other documents bearing a magnetic stripe have long been used for a variety of different purposes. Such magstripe cards are currently used in large numbers, for example in the forms of credit cards, debit cards, tickets, passes, I.D. cards and so on. Typically the magnetic stripes of such cards carry digitally recorded data, 20 for example relating to the use of the card, the assigned user, and so on.

25 Although magnetic stripe documents are widely and successfully used in commerce and industry, various forms of copying have become common place. The aggregate losses from fraudulently copied magstripe cards are very large. Consequently, a continuing need exists for a practical and economical system and method to reliably identify, and thus verify or authenticate magstripe documents.

Over the years, there have been numerous proposals for verifying documents, including techniques for authenticating magnetic stripes. A substantial number of prior proposals have been based on a concept of using certain magnetic characteristics of the magnetic stripe to verify documents, as cards. In that regard, it has been determined that magnetic stripes possess inherent, substantially unique, magnetic characteristics that can be repeatedly sensed. Over the years, these characteristics have been recognized as contributing a signal component sometimes considered to be noise in the sensed analog signal. Thus, along with the sensed data, a repeatable signal component (noise) also is present. Essentially, just as the magnetic characteristics of individual stripes are distinct, the resulting "noise" signals are somewhat unique and can characterize or identify magnetic stripes. Thus, it has been proposed to employ such magnetic characteristics and the resulting "noise" signals as a basis for identifying and verifying individual magnetic stripe documents. In some instances, the general technique has been compared to the science of human fingerprinting, that is, involving the use of a somewhat unique physical characteristic for purposes of identification. However, although various verification techniques and structures, based on the noise or characteristic magnetic component of a sensed magstripe signal have been proposed, they have not been widely accepted.

One prior proposal involved using a separate non-data magnetic stripe placed on a document specifically for purposes of identifying the document. Other proposals have involved

various treatments of the magnetic stripe, usually involving the signals that are recorded and sensed from magnetic stripes.

Typically, the magstripes on conventional magstripe cards are divided into parallel tracks that are digitally recorded and sensed. Many of the prior proposals for magstripe document verification have involved the record of one track of the magnetic stripe in the form of digital data represented by magnetic transitions along the length of the magnetic stripe.

Portions of analog signals sensed from the magnetic track transitions, or other portions of the signal have been proposed for use in characterizing the card or document. For example, on a time base, peaks in the sensed analog signal (representing magnetic transitions) have been proposed for use in verifying the magnetic stripe. Other proposals have suggested using other portions of the sensed analog signal from one of the magnetic tracks. For example, the relatively flat signal portions representative of magnetized regions of the stripe (located between magnetic transitions) have been proposed for use.

Various techniques also have been proposed for attaining more consistent results in sensing the magnetic characteristic signals. For example, techniques have included: averaging the results of multiple sensings, oversampling (increased sampling as by a factor of one hundred) and using a phase locked loop to control sampling. It also has been opined that for identification and verification purposes, sizable

variations are quite acceptable between individual sensings of magstripe characteristics.

In the final analysis, as indicated above, in spite of the numerous structures and techniques proposed for magstripe fingerprinting, the concept has not gained widespread acceptance. That is, using the so called "remanent noise" in a signal sensed from magstripes to verify individual documents has not come into widespread use. Rather, although numerous proposals have been suggested for such operation, the technique simply has not gained significant commercial or industrial acceptance.

Typically, magnetic stripe fraud involves variously copying the recorded data (including verification data) in either a digital or analog form and using it to verify a transaction. Thus, a considerable need exists for a reliable system of combating fraud related to magstripe documents, which fraud may involve various forms of copying, duplicating or misdirecting data.

In general, the system of the present invention is based on recognizing the various problems of using the repeatable characteristics of a magstripe for purposes of verification, for example, in broad commercial and industrial applications. In that regard, it has been determined that many problems arise in the arenas of broad industrial and commercial use which are not apparent in the laboratory.

One major consideration relating to the extensive use of magnetic characteristics for card verification involves the number of cards used in a system. For example, a commercial

credit-card system may be required to accommodate many thousands of individual cards operating randomly in combination with hundreds, if not thousands, of individual processing units. Furthermore, in an extensive system, reliability becomes exceedingly important, particularly in the realms of financial and security transactions, as are involved with financial cards.

In general, the system of the present invention involves improvements that enable magnetic characteristic verification techniques to operate successfully and reliably in the realms of widespread commercial and industrial applications. Specifically, the processes and systems of the present invention are directed to developing reliable magnetic stripe verification in a large scale system.

As disclosed herein, repeatable magnetic characteristic signals (resulting from specific characteristic features of the magstripe) may be selected from defined areas of a digitally-recorded magnetic stripe. The defined areas may be located between magnetic data transitions. Such defined areas of the stripe may be magnetized to a level of saturation and accordingly produce relatively flat (stable) sections in the sensed analog signal. Although these signal sections are relatively flat, they manifest a low level signal (noise) representative of the repeatable magnetic characteristics or features of the stripe. Thus, such signal sections may be used to reliably characterize each magnetic stripe in a manner somewhat analogous to a fingerprint. As disclosed herein, further reliability is attained by testing signal amplitude

and symmetry characteristics as well as challenging digital copies by excessive similarity tests involving recently sensed characteristics..

Regarding the basic characteristic determination, as disclosed herein, after sensing a magstripe to produce a magnetic analog signal (typically containing digital data) a target number of samples are taken from several relatively flat sections of the analog signal using a frequency lock loop. Individual samples in each group are converted to a digital form, then selectively processed to obtain a predetermined subset of samples. The predetermined subset of digitized samples is then further processed by offset selection to accomplish a sub-subset of digitized samples that become a component of a characteristic designation used for identification. That is, several sub-subsets of digitized samples are collected to form part of an identifier for the magstripe-bearing card.

With the magnetic characteristic resolved to a digital representation, dynamic range information is extracted from the digitized samples to supplement the magnetic characteristic in the representative identifier. In the disclosed embodiment, the dynamic range information is based on amplitude symmetry or waveform characteristics as disclosed in detail below. Generally, by including dynamic range information in the identifier for a magnetic stripe, certain forms of the copied identifier can be distinguished as disclosed in detail below.

Other methods of copying may present the identifier in a digital form, for example, in the ultimate form for the test comparison. As disclosed herein, such copying is challenged by comparing the presented identifier with recently sensed
5 identifiers which are the likely source of copies. If the degree of similarity is excessive, copying is suggested. Otherwise, the freshly sensed identifier is tested by correlation with reference identifiers to verify the card or other document.

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings, which constitute a part of this specification, exemplary embodiments exhibiting various objectives and features hereof are set forth, specifically:

15 Figure 1 is a block diagram of a system constructed in accordance with the present invention;

Figure 2 is a graphic representation of a portion of a data record on a magnetic stripe track as shown in Figure 1 and used in accordance herewith;

20 Figure 3 is a grossly-enlarged pictorial view of a magnetic data pattern showing a small portion of a stripe track as graphically illustrated in Figure 2;

Figures 4A and 4B show a related pair of graphic representations relating to a small portion of a track as
25 illustrated in Figure 2;

Figure 5 is a block diagram indicating one form of characteristic extraction circuit as may be utilized in the system of Figure 1;

Figures 6A, 6B, 6C, 6D and 6E are a series of graphic representations relating to a small fragment of a representative analog signal from a magnetic stripe track as illustrated by Figure 4;

5 Figure 7 is a block diagram indicating one form of identifier forming circuit as may be utilized in the system of Figure 1;

Figure 8 is a flow diagram illustrating an exemplary process of the present invention as may be used in the system of Figure 1; and

10 Figures 9A and 9B constitute a flow diagram of an exemplary process in accordance herewith.

Description of the illustrative embodiments

15 As is required, detailed illustrative embodiments of the present invention are disclosed herein. However, documents, physical magnetic systems, data recording formats, and operating structures in accordance with the present invention may take a wide variety of different forms, some of which may be quite distinct from those of the disclosed embodiments.

20 Consequently, the specific structural and functional details disclosed herein are merely representative; yet in that regard, they are deemed to afford the best embodiments for purposes of disclosure and to provide a basis for the claims

25 herein which define the scope of the present invention.

In Figure 1, a magnetic stripe card 10 (left) is shown exemplifying a document, entering (arrow 12) a sensing unit 14. The magnetic stripe card 10 may take the form of a

conventional bank card comprising a wallet-sized sheet of plastic material bearing the magnetic stripe 16. In the exemplary form, the card 10 is embossed and printed with indicia 17 to indicate the issuing entity, the holder's name, the account number and so on. The magnetic stripe 16 on the card 10 has at least one track recorded with digital data and possesses a repeatable magnetic characteristic as discussed above.

Functionally, the sensing unit 14 produces at least one analog signal AS from a recorded track that carries both the recorded digital data DD of the stripe 16 and representations of the repeatable magnetic characteristic MC. In accordance herewith, the analog signal AS is processed to provide three digital representations, i.e. digital card data (e.g. account number, etc.) magnetic characteristic data and waveform or range characteristic data. The card data is used to process the card, and possibly to enable or reflect a transaction. The characteristic data (magnetic and waveform) serves to verify the card, as against, direct and indirect copies, as well as misdirected data. Furthermore, in accordance herewith, representations of the characteristic data are compared with prior presentations for excessively high degrees of similarity or exactness, which may suggest copying. Note that herein, similar designations are used for data and representative signals.

Returning to the structure of FIGURE 1, as indicated, the sensing unit 14 comprises a magnetic stripe read unit for sensing the magnetic stripe 16 on the card 10 to produce the

analog signal AS. Note that with repeated sensings, even though the digital data DD recorded by the stripe 16 may be changed with time, the magnetic characteristic MC can be extracted as a repeatable component of the sensed analog signal AS. As indicated above, sometimes the magnetic characteristic signal MC (representing the characteristic MC) has been considered noise. However, the signal MC manifests a characteristic feature of the magnetic stripe 16 and in accordance herewith serves as one basis to verify the card 10. As disclosed in detail below, from the analog signal, the signal components DD and MC are separately extracted by a pair of extraction circuits 18 and 20 respectively. The dynamic range data DR characterizing the analog signal AS (as by waveform amplitudes) is extracted by extraction circuits 25.

From the circuit 18, the digital data signal DD is provided to a control and transaction system 28 for further processing as described below. In various applications, the data signal DD may be variously employed, as for example, to support a credit transaction or drive an automatic teller machine.

As described in greater detail below, in the extraction circuit 20, the characteristic analog signal AS is sampled during defined sampling intervals SI, the samples being digitized to accomplish groups or sets of digitized samples DS. Selected samples from the sets representing the magnetic characteristic, are developed by forming circuits 22 and combined with range data signals (circuits 25) in the circuits 22 to provide a sensed test word STW.

Representative signals for the "sensed" test word, termed STW, are applied to a correlation circuit 24. To function, the correlation circuit 24 also receives at least one "reference" test word RTW from a source unit 26. The
5 reference source unit 26 may take a variety of different forms. For example, a sensed test word STW could be formed as described herein then recorded digitally on the card 10 for direct provision by the unit 26 as a reference test word STW. However, in the currently preferred embodiment, the reference
10 unit 26 accesses a data bank (not shown) to provide several reference test words RTW for correlation with a freshly sensed test word STW as described below.

In addition to the correlation of reference and sensed test words by the correlation unit 24, a preliminary test of the words is performed by a bit-by-bit coincidence detector
15 27. Basically, the detector 27 tests the sensed test word STW against the reference test words RTD for degrees of exact similarity which may suggest fraud. If the test is successful (no excessive similarity), then independently, the correlation
20 unit 24 correlates the test words. If that test is successful, the central and transaction system 28 is signaled.

Note that the control and transaction system 28 may incorporate offsite components and furthermore, may incorporate or overlap apparatus involving the source unit 26.
25 For example, the transaction system 28 may be integral with the reference unit 26 comprising a structure for addressing a data bank containing data on a card user's account number. As a consequence, the data bank provides at least one reference

test word for comparison tests. Also note that such data can be combined with other identifiers, e.g. PIN, PAN, etc. to combat fraud otherwise by various comparisons.

The control and transaction system 28 also may embody various other operating equipments or systems, e.g. automatic teller machines, entry or access controls, card verification units, and so on. Thus, the digital data signal DD is processed and variously utilized by the control and transaction system 28.

As suggested, the stripe 16 (FIGURE 1) includes a plurality of individual record tracks. A single track is treated herein. Specifically, a typical format for a track 29 (FIGURE 2) of the magnetic stripe 16 is fragmentarily illustrated (not to scale). Initially, a section 30 stores a series (e.g. approximately twenty) of leading zeros designated LZs. Analog signal AS from the leading zero section 30 conventionally synchronizes the timing for subsequent operations. However, in accordance herewith, the uniform digital recording of the leading zeros section 30 also is used to provide the magnetic characteristic data MC.

Next in the track 29 format of Figure 2, a section 32 carries a start sentinel SS. Thereafter, a section 35 stores a primary account number PAN for the assigned card user. The next section 36 stores a field separator FS which is followed by a section 38 for storing various additional data AD. The sections are well-known and are defined by the International Standards Organization. However, as shown, they are merely

illustrative and any of wide variety of formats may be employed in systems of the present development.

In relation to the digital data recorded on the stripe 16, for example, in the track 29 (FIGURE 2), devices are well-known for actually viewing the magnetic configuration including the digital recording pattern. Magnetized regions are clearly visible separated by magnetic transitions. Such a view is represented in Figure 3 with individual magnetic transitions 40 and 41 appearing between magnetized regions 42. Note that scratches 44 also appear in the figure.

In accordance herewith, it is important to understand that magnetic characteristic data MC is sensed from the magnetized regions 42 (FIGURE 3) in the leading zero section 30 (FIGURE 2) of the track 29. The regions 42 translate to relatively flat, or stable sections, of the signal AS.

Figure 4A shows a grossly enlarged fragment 39 of the magnetic stripe track 29. A pair of magnetic transitions 40 and 41 (representing digital data) are indicated, defining a magnetized region 42 between them. Incidentally, individual magnetic particles 46 (right) also are indicated in the cross section. Generally, it has been understood that the inherent variations of these particles 46 at specific locations account for the magnetic characteristic MC (fingerprint) of the stripe 16.

Below the track fragment 39 (FIGURE 4A), an aligned waveform 50 (FIGURE 4B) illustrates the representative analog signal AS selectively showing signal amplitude variations 48 from a region 42 (FIGURE 4A). Of course, other portions of

the analog signal AS also contain such variations in relation to the pulses 52 and 54, however, the variations 48 are of primary interest and therefore are shown isolated in the idealized waveform 50. Thus, the pulses 52 and 54 represent the transitions 40 and 41 as digital data DD and the variations 48 indicate the magnetic characteristic (noise) of interest. Recapitulating, in the present embodiment, the magnetic characteristic MC (FIGURE 4B) is taken from the variations 48 in the relatively flat portions 56, (termed interspersed portions IP) of the analog signal AS representing the leading zeros section 30 (FIGURE 2) of the track 29.

For the magnetic characteristic MC, as mentioned above, digital samples of the variations 48 are formed into digital representations. For the dynamic range information DR, waveform characteristics of the analog signal AS are reduced to digital representations. For example, as disclosed below, the dynamic range information might for example take the form of relative peak amplitudes or line offset ratios in the analog signal AS. Specifically, referring to Figure 4B, the range information might constitute a ratio of the peak amplitudes of pulses 52 and 54 as well as ratios of pulse amplitude to center line offset at the section 56. Such information may be represented as a few binary bits while, the magnetic characteristic MC might be represented by several bits, e.g. twenty. Accordingly, an exemplary test word STW of 24 bits may be formulated as follows:

TEST WORD

100110101100010110110100

****MC*****-DR-

A specific test word TW thus characterizes each magnetic stripe card and is stored for reference comparisons as

5 indicated above. However, in accordance herewith, it has been recognized that a prior test word STW might be copied in an effort to support a fraudulent transaction. Generally, such a copied word will result in a closer correlation than if the test word STW were freshly generated. That is, by digitally

10 copying a test word, an exact coincidence may occur, which event would be very unlikely in sensing and developing a fresh test STW. Consequently, in accordance herewith, a record of reference test words RTW (e.g. original and recently used words) is stored for bit-by-bit correlation with words

15 asserted as proper sensed test words to support transactions. The occurrence of a very close bit-by-bit comparison suggests fraudulent digital copying of a test word. For example, a dissimilarity of only four or less bits between a sensed test word STW and an asserted reference test word RTW may suggest
20 fraud.

In accordance herewith, asserted test words STW first are compared with reference test words RTW seeking excessive similarities. In the event of a near identity, the transaction is denied based on the suggestion of digital
25 copying. Essentially, a drop off list of the last several sensed test words STW may be stored as reference test words RTW for comparison. If the bit-by-bit comparison indicates sufficient dissimilarity, the system then proceeds with a

correlation of a reference test word RTW with the sensed test word STW, asserted as being freshly sensed.

Recognizing that a variety of structures and processes may be employed to develop test words with magnetic characteristic data MC and dynamic range data DR, techniques of the disclosed system will now be considered. Referring to FIGURE 4B, the peaks of the pulses 52 and 54 are detected in the extraction circuits 20 (FIGURE 1) to define a sampling interval SI. The actual sampling operation is performed during each sampling interval SI, also by the extraction circuits 20 (Figure 1) an illustrative form of which is shown in Figure 5. Consider the operation with concurrent reference to Figure 6 illustrating the various signals in an idealized form, and not to scale. Also, note that the scale of Figure 6 is grossly enlarged with respect to the curves of Figure 4, and the curves of Figure 6 are broken to simplify the representations.

During the sampling interval SI (FIGURE 6A, time 62) the analog signal AS is applied to a peak-to-peak detector 60 (FIGURE 5). Such circuits are well-known and can function in accordance herewith to define intervals between recurring peaks in the analog signal AS (Figures 4B and 6B). Accordingly, the peak detector 60 provides binary time signals 62 (Figure 6A) defining each sampling interval SI.

During a defined sample interval SI (peak-to-peak Figure 6A), the analog signal AS (Figure 6B, curve 64) is sampled to provide approximately one hundred twenty-eight digital samples DS (Figure 6C not to scale). The individual samples are

defined by a frequency locked loop 66 (FIGURE 5) incorporating an oscillator (not shown). Forms of such circuits are well-known for defining a target number of cycles during each interval.

5 In the illustrative system, the frequency lock loop 66 has a target of defining one hundred twenty-eight samples during each sample interval SI (Figure 6A). Thus, approximately one hundred twenty-eight samples are supplied from the loop 66 (Figure 5) to an analog-to-digital converter
10 68 during each sampling interval. However, variations in the system, medium and so on normally account for more or less than one hundred twenty eight samples actually being accomplished.

 The A/D converter 68 (Figure 5) converts each sample
15 (analog) to a digital form, for example, defined by a number of binary bits. Note that although converted to a digital form, the samples DS are illustrated as vertical bars in Figure 6C. Signals representative of the digitized samples DS are supplied from the extraction circuit 20 (Figure 1) to the
20 extraction circuit 25 and the test word forming circuit 22.

 In accordance herewith, a predetermined number of digitized samples DS (subset) is to be consistently used for each sampling interval SI. To accomplish the predetermined number of samples DS for each sampling interval SI, a re-
25 sizing operation is performed to produce a subset (e.g. "64") from the varying total number of samples (e.g. "128±"). The re-sizing operation is performed in the characteristic forming circuit 22 (Figure 1) as will be considered below. However,

preliminarily, some further graphic considerations are provided.

In the disclosed embodiment, the samples for representing the magnetic characteristic MC are taken from the last eight interspersed portions 56 (FIGURE 4B) of the leading-zeros section 30 (FIGURE 2) of the track 29. These signal portions 56 represent the magnetized regions 42 (Figure 4A) in the leading zeros section 30 of the track 29 located between data transitions 40 and 41 .

Note that Figures 4 and 6 represent a single sampling interval SI. Accordingly, as explained in detail below, the last eight intervals in the leading zeros section 30 are stored in the forming circuit 22 (Figure 1) and processed to accomplish a series of binary words that are then combined with the dynamic range data to form the test word STW.

The forming circuit 22 (Figure 7), includes a control unit 80 (lower left) coupled to receive sample interval signals SI along with a signal from a sentinel detector 82 which in turn receives the analog signal AS. In operation, the detector 82 senses a signal representative of the sentinel SS (Figure 2) indicating the end of the leading zeros. The end of the leading zero, portion 30 (Figure 2) is thus indicated to the control unit 20.

The control unit 80 (Figure 7) also is connected to a register 86 which receives sets of digitized samples DS from the analog-digital converter 68 (Figure 5). The register 86 (Figure 7) is basically an overflow register, which retains only the last eight sets of received digitized samples DS for

processing. The stored eight sets of digitized samples DS are then bulk transferred from the register 86 (Figure 7) to a working storage 88 for processing. The working storage 88 is connected to interface an Nth sample processor 90 and an
5 offset processor 92. The processors 90 and 92 are also connected to the control unit 80.

Essentially, sets (e.g. "8") of the digitized samples DS (Figure 6C) are first processed by the processor 90 (Figure 7) to provide subsets consistently including a predetermined
10 number of digitized samples, e.g. "64" samples. The resulting subsets of digitized samples DS are further reduced to sub-subsets by the processor 92 e.g. "24" samples. The second reduction limits samples to central samples, those well within the "flat" portions of the analog signal AS. Essentially,
15 each set of digitized samples DS is reduced first to a specific-number sub-subset of samples then to provide a central sub-subset as the ultimate magnetic characteristic MC. The sub-subsets of digitized samples DS are accumulated in the storage 94 which also receives the digitized dynamic range
20 data DR to form the test word STW.

It is to be noted that certain elements of the forming circuit as shown in Figure 7 have been separately shown merely for purposes of convenient explanation. As throughout, in an operating system, various elements might be incorporated or
25 combined. Of course, a wide variety of different processing techniques may be utilized in accordance herewith to accomplish the process as explained in greater detail below with reference to a logic flowchart.

In view of the above descriptions, a complete understanding of the disclosed system can now best be accomplished by pursuing an explanation of the process and providing further component descriptions where pertinent.

5 Accordingly, assume the presence of a magnetic stripe card 10 (Figure 1) bearing a magnetic stripe 16 with a digitally recorded track 29 (Figure 2). As represented by a block 100 (FIGURE 8), the unit 14 (Figure 1) senses the leading zeros section 30 as the portion of the analog signal AS (Figure 4B) which is applied to: the data extraction circuits 18 (Figure 1), the magnetic characteristic extraction circuits 20 and the range data extraction circuits 25. The data extraction circuits 18 extract the digital data DD which is supplied to the central and transaction system 28. Such data includes representations for accessing a data bank to provide reference test words RTW as explained above.

15 The extraction circuits 20 first digitize the analog signal AS (Figure 8, block 102) storing the last eight sets ("128±") of samples (block 104). The sets of samples are then processed, set by set (block 106). Essentially, the sets are reduced to subsets of "64".

20 This operation is performed because even though the sampling intervals are controlled by a frequency lock loop, in an operating environment, the number of samples taken during a sample interval may vary, e.g. potentially including either a few additional samples or a few less samples. Re-sizing to obtain a specific number of samples (e.g. "64") has been determined to be somewhat critical in certain applications.

The processor 90 (Figure 7) accomplishes the subset selection and may simply be implemented to execute the logic of Figure 8. An initial query, (block 108 Figure 8) indicates three possibilities with respect to the set of digitized samples. The set might either: (1) be equal to the target number of one hundred twenty-eight, (2) be more than the target number or, (3) be less than the target number.

If the target number of one hundred twenty-eight was accomplished, the process simply proceeds to a junction 110 (Figure 8, lower center) from which a subsequent reduction step occurs. However, if the number of actual digitized samples in the set is less than one hundred twenty-eight, the process proceeds to a step of a query block 112 allowing three different possibilities, i.e. the samples number either: one hundred twenty-five, one hundred twenty-six or one hundred twenty-seven. Of course, greater numbers of displacements from the target number can be accommodated; however, for purposes of illustration variations of up to "three" samples DS are treated as examples which could be expanded.

Assume the deviation from the target number is one hundred twenty-five samples. In that event, the process proceeds to a step as illustrated by a block 114 which is illustrated graphically in Figure 6D. Basically, alternate samples are dropped (odd or even), with certain added exceptions to attain the predetermined number, e.g. sixty-four. However, in adding or deleting samples at spaced-apart locations, the odd-even sequence shifts with each deletion or addition. For simplification, assume a set of fourteen

samples and a need for a subset of eight samples. If "odd" samples are initially selected, a switch to "even" samples is made with an addition. Specifically, the underscored samples are selected as eight:

5

To add samples, select the underlined:

1 2 3 4 5 6 7 8 9 10 11 12 13 14.

10 To remove samples a similar alternate selection is employed. For example, to obtain a subset of eight samples from a set of seventeen the pattern might be as follows:

To delete samples, select the underlined:

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17.

15

Thus, according to the process, alternate samples are taken with additions to accomplish a subset of exactly sixty-four digitized samples DS. With such a predetermined subset, the operation proceeds to the junction 110, again, treated subsequently.

20

If the initial set of digitized samples DS constituted one hundred twenty-six samples, the process (FIGURE 8) proceeds to a step represented by a block 116. Here, the process again involves selecting alternate samples DS along with additional samples to accomplish the desired subset, e.g. sixty-four.

25

Similarly, if one hundred twenty-seven samples were attained, the process proceeds to a step illustrated by a

block 118 indicating an alternate selection, again adding to
attain sixty-four. Thus, by using spaced-apart or distributed
normally-rejected samples to supplement the selected samples,
subsets SDS of a precise number are accomplished by the
5 processor 90.

As indicated above, the actual number of samples in a set
also may exceed the target number of samples. In that event,
the process proceeds to a query block 120 (Figure 8, upper
right) indicating a step of identifying whether the excessive
10 number of samples is "one," "two" or "three." If "one" excess
sample exists, the operation proceeds to a step of block 122
which involves selecting alternate samples DS and deleting to
attain the desired sixty-four. Thus, a precise subset of "64"
samples DS is attained and the operation proceeds to SDS the
15 junction 110.

Similar deletions occur in the event of two or three
excess samples as represented by the blocks 124 and 126. In
such events, samples are dropped in addition to the alternate
selection. Thus, with a subset of precisely sixty-four
20 samples DS, the process proceeds from the junction 110.

With each subset of precisely sixty four digitized
samples, the next phase of the process is performed by the
processor 92 (Figure 7) to accomplish a sub-subset by offset
selection. In that regard, several initial and final
25 digitized samples DS are dropped, leaving a sub-subset of
digitized samples DS taken from the relatively-stable
(central) portion 56 (FIGURE 4B) of the analog signal AS.
Thus, the interspersed portion of the sample section is

selected representing the central magnetized region 42
(Figure 4A) as explained above.

The operation of the offset processor 92 may be
relatively simple as represented by a block 128 in Figure 8.
5 Specifically, a central sub-subset of digitized samples DS,
e.g. twenty-four is selected as indicated in Figure 6E from
each stored subset of sixty-four.

With the accomplishment of each sub-subset (twenty-four
samples DS) the process proceeds to a query block 130 (Figure
10 8, lower left) representing the step of determining whether
all eight sub-subsets have been processed. When the last of
the eight sets is complete, they represent the magnetic
characteristic MC to be combined with the range data by the
circuit 22 to provide the test word STW. The operation is
15 represented in FIGURE 8 by a block 132.

To form the digitized dynamic range data as a digital
word, digitized samples DS stored in storage 88 (FIGURE 7) are
provided to the extraction circuit 25. The digitized samples
define the analog signal AS and accordingly are processed to
20 characterize the dynamic range (waveform features) of the
analog signal. In the disclosed embodiment, two amplitude
ratios are used as the range data. First, as illustrated in
FIGURE 4B, amplitude symmetry is taken as a ratio of the
positive-going pulse 52(x) to an adjacent negative-going pulse
25 54(a). Thus, in the present embodiment, amplitude symmetry is
determined by a ratio of x/a . As indicated, available digital
representations of these values are held in the storage 88
(Figure 7) and accordingly, the extractions circuits 25

(Figure 1) simply receive such values to provide the ratio calculation after which the value is reduced to a few bits. The waveform component of the digitized dynamic range data DDR is formed somewhat similarly.

5 In the disclosed embodiment, the waveform characteristic actually is a standard parameter, specifically identified as "ISO/IEC Standard 7811-6, Table 1 - parameter U_{i6} ". The indicated parameter has other uses in relation to magnetic tape; however, in the illustrative embodiment it serves as a
10 specified waveform characteristic. Referring to Figure 4B, the selected parameter is the ratio of a/b where b is a central derivation in the section 5 (FIGURE 4B). With the range data characteristic so formed, it is merged with the magnetic characteristic data by the forming circuits 22. The
15 merger may simply involve joining the representative data as the sensed test word STW.

 To consider an overall operation, assume the card 10 (FIGURE 1) is in a raw state and is to be processed for issuance. Initially, in accordance herewith, the stripe 16 is
20 recorded with digital data DD (FIGURE 9A, block 148). Next, the card is sensed and a test word STW is formulated, as described above, characterizing the stripe 16. The formation of the test word, represented as a process step by a block 150 in FIGURE 9A is followed by storing the test word STW as a
25 reference test word RTW (block 152) available in the future from the reference unit 26 (FIGURE 1) addressed by the digital data DD.

With the card recorded and the reference test word RTW stored, the card is issued to a holder. In Figure 9A, the issuing operation is represented by a block 154.

5 In due course, the card is presented, for example, to support a transaction as indicated by the block 156. Accordingly, the card is processed by structure in accordance with Figure 1, for verification.

10 The card 10 is sensed for the analog signal AS which is to provide the digital data DD (identification) and the sensed test word (block 158).

15 Using the digital data DD, the control and transaction system 28 (Figure 1) fetches at least one reference test word RTW (initially only one, however, later to include several recent test words) from the source unit 26 (including a central data bank), supplied to the coincidence detector 27. See the block 160.

20 The sensed test word STW and the reference test words are supplied to the detector 27 comparison. The detector 27 executes a bit-by-bit comparison between each referenced test word RTW and sensed test word STW seeking coincidence. Structurally, the detector 27 may simply involve a stepping register for moving the referenced test words RTW through stages for repeated comparison with the sensed test word STW to indicate coincidence between individual binary bits. Each
25 lack of a bit coincidence is tallied. The processed step is illustrated by block 162 in Figure 9A.

As explained above, total coincidence between one of the reference test words RTW and the sensed test word STW is a

very strong indication of digital copying. Essentially, although the nature of the "fingerprint" system involves identification by a degree of coincidence, identity of coincidence is exceedingly unlikely. Accordingly, the
5 detector 27 is set to count bit-by-bit deviations and provide a represented total to the correlation unit 24. Only in the event of less than substantial coincidence between the sensed test word STW and each of the referenced words RTD does the unit 24 proceed. Such deviation, indicates the lack of
10 digital copying from a recently sensed test word. On the contrary, a coincidence or near coincidence (low number of deviations) prompts the detector 27 to signal the system 28 indicating a rejection of the transaction. These operations are represented in Figure 9A by the query block 164 and the
15 reject block 166. A proper comparison (with significant deviations) prompts the correlation unit 24 (FIGURE 1) to proceed as indicated by the block 168 (note a transition from Figure 9A to Figure 9B).

The continuing test is executed by the correlation unit
20 24 (Figure 1) illustrated as two steps in FIGURE 9B, i.e. correlation of the dynamic range information DR (blocks 170, 172 and 174) then correlation of the magnetic characteristic MC (blocks 176, 178 and 180). Of course, the nature and degree of an acceptable magnetic correlation will depend on
25 design considerations for the specific system. However, generally, even a relatively loose degree of magnetic correlation indicates lack of copying.

With the occurrence of an approved transaction, the sensed test word STW, as provided, is stored (Figure 9B, block 182) for subsequent use as a referenced test word RTW. In that regard, the sensed word is passed from the correlation
5 unit 24 through the transaction system 28 to the source unit 28 for storage. Thus, a limited list or group of reference test words RTW are provided for subsequent comparison. In that regard, generally it has been determined expedient to limit the number of active reference test words to a
10 predetermined number. Consequently, with the storage of a fresh test word, a test may be performed limiting the active group to the predetermined number (Figure 9B, block 184). Note that the predetermined number, i.e. the number of active referenced test words utilized, involves various design
15 criteria with considerations as to frequency of card use, values involved, and so on. As indicated, merely for example, six or eight words may be adequate.

As a final step in the process, a card 10 may be released as indicated by block 186 in Figure 9B. Thus the process is
20 complete.

In executing the process, it is noteworthy that the implementing components may be variously located. Typically, locations will involve a central station serving a multitude of remote terminal stations, e.g. merchant locations. In
25 accordance with one embodiment, implementing circuits and so on to formulate the sensed test word STW and the digital data DD are located at card terminals, with the balance of the

system located at a central terminal. However, several other variations may be practical for individual systems.

In view of the above explanation of an exemplary system, it will be appreciated that other embodiments of the present invention may be employed in different applications to verify, authenticate, identify or confirm documents, particularly magnetic stripe-bearing cards. While exemplary operations have been stated herein and certain detail structures have been disclosed, the appropriate scope hereof is deemed to be in accordance with the claims as set forth below.

1 **WHAT IS CLAIMED IS:**

2
3 1. An identification system for identifying documents
4 bearing a magnetic stripe recorded with digital data and
5 having a repeatable magnetic characteristic, comprising:

6 a magnetic stripe sensor for sensing the magnetic stripe
7 to provide an analog signal representative of the recorded
8 digital data and the repeatable magnetic characteristic;

9 a digitizer for sampling the analog signal to provide
10 digitized samples indicative of the repeatable magnetic
11 characteristic;

12 a waveform circuit for providing range data
13 characteristic of the analog signal; and

14 a storage for storing representations of the digitized
15 samples and the range data as identification data to identify
16 the document.

17
18 2. An identification system according to claim 1
19 wherein the magnetic stripe is recorded with a series of
20 leading zeros and the digitizer samples the analog signal in a
21 portion representing the series of leading zeros.

22
23 3. An identification system according to claim 1
24 wherein the magnetic stripe is recorded with digital data
25 represented by magnetic transitions and the digitizer samples
26 a portion of the analog signal representing spaces between
27 said magnetic transition to provide a digitized samples
28 indicative of the repeatable magnetic characteristic.

1 4. An identification system according to claim 1
2 wherein the documents comprise magnetic stripe cards and
3 wherein the digital data recorded on the magnetic stripes
4 includes data for fetching identification data from the
5 storage.
6

7 5. An identification system for identifying documents
8 bearing a magnetic stripe recorded with digital data and
9 having a repeatable magnetic characteristic, comprising:

10 a magnetic stripe sensor for sensing the magnetic stripe
11 to provide an analog signal representative of the recorded
12 digital data and the repeatable magnetic characteristic;

13 a magnetic characteristic circuit providing magnetic
14 characteristic representations indicative of the repeatable
15 magnetic characteristic;

16 a waveform circuit providing range representations
17 indicative of a characteristic of the analog signal; and

18 a forming circuit to provide document identification
19 representations based on the magnetic characteristic
20 representations and the range representations to identify the
21 documents.
22

23 6. An identification system according to claim 1
24 further including storage to store document identification
25 representations and a comparison structure for comparing
26 document identification representations from the storage with
27 document identification representations from the forming
28 circuit to verify a document.

1 7. An identification system according to claim 6
2 wherein the storage stores a plurality of document
3 identification representations for comparison with a document
4 identification representation from the forming circuit and
5 wherein verification requires a degree of dissimilarity.
6

7 8. An identification system according to claim 5
8 wherein the magnetic characteristic circuit provides magnetic
9 characteristic representations from the analog signal at
10 substantially flat sections to produce a predetermined number
11 of digital samples.
12

13 9. An identification system according to claim 5
14 wherein the waveform circuits provides range representations
15 indicative of amplitudes of the analog signal.
16

17 10. An identification system according to claim 5
18 wherein the waveform circuit provides range representations
19 indicative of ratios of amplitudes of the analog signal at
20 predetermined locations.
21

22 11. A system for use with a card bearing a magnetic
23 stripe having a repeatable magnetic characteristic and
24 recorded with digital data in the form of magnetic
25 transitions, said system for providing a sensed characteristic
26 identification for the card, comprising:

27 means for sensing said magnetic stripe to provide
28 representations of digitally recorded data and representations

1 of the repeatable magnetic characteristic in the form of
2 digital sample signals;
3 means for selectively storing card identification words
4 formed from the digital sample signals to manifest the
5 repeatable magnetic characteristic of a card and amplitude
6 characteristics of the digital sample signals.

7
8 12. A process for identifying documents bearing a
9 magnetic stripe having a distinct magnetic characteristic that
10 is capable of repeated sensing to identify individual
11 documents, said process including the steps of:

12 sensing the magnetic stripe to produce a representative
13 analog signal manifesting the distinct magnetic
14 characteristic;

15 providing magnetic characteristic representations
16 indicative of the distinct magnetic characteristic;

17 providing range characteristic representations indicative
18 of the analog signal regarding amplitude; and

19 providing identification representations based on the
20 magnetic characteristic representations and the range
21 characteristic representations to identify the documents.

Abstract

Magnetic stripe documents are identified and authenticated on the basis of repeatable magnetic characteristics of a stripe recorded with digital data and waveform characteristics of the sensed digital data. Stripes are sensed to provide an analog signal, only the portion storing leading zeros being used. Cyclically, the leading-zero portion is sampled and digitized to provide a target number of samples using a frequency locked loop. The target number of samples is then reduced by a selection process that attains a predetermined number of digital samples from central locations in magnetized portions of the record specifically, spaces between data transitions. Selected groups, each of a predetermined number of digital samples, are then combined to provide magnetic characteristic data. Such data is then combined with waveform data (range) to provide an identification word. Documents are verified by correlating reference and sensed identification words. One or several reference identification words also may be tested for excessive similarity suggesting a fraudulent copy.



FIG. 1

660000-71212260




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5




FIG. 7

FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D





FIG. 6E







FIG. 8

FIG. 9A






FIG. 9B

POWER OF ATTORNEY BY INVENTOR

Assistant Commissioner for Patents
Washington, D. C. 20231

Sir:

As the named inventor in the application for United States Letters patent entitled MAGNETIC STRIPE AUTHENTICATION AND VERIFICATION SYSTEM which application papers were filed June 3, 1999, I hereby appoint: Byard G. Nilsson, Reg. No. 17,350; Harold E. Wurst, Reg. No. 22,183; Robert A. Green, Reg. No. 28,301; Stephen D. Burbach, Reg. No. 40,285; John Wurst, Reg. No. 40,283; Ross Snyder, Reg. No. 37,730; Ivan Posey, Reg. No. 43,865; Derrick Reed, Reg. No. 40,138; Gordon D. Coplein, Reg. No. 19,165; William F. Dudine, Jr., Reg. No. 20,569; Michael J. Sweedler, Reg. No. 19,937; S. Peter Ludwig, Reg. No. 25,351; Paul Fields, Reg. No. 20,298; Joseph B. Lerch, Reg. No. 26,936; Melvin C. Garner, Reg. No. 26,272; Ethan Horwitz, Reg. No. 27,646; Beverly B. Goodwin, Reg. No. 28,417; Adda C. Gogoris, Reg. No. 29,714; Martin E. Goldstein, Reg. No. 20,869; Bert J. Lewen, Reg. No. 19,407; Henry Sternberg, Reg. No. 22,408; Peter C. Schechter, Reg. No. 31,662; Robert Schaffer, Reg. No. 31,194; David R. Francescani, Reg. No. 25,159; Robert C. Sullivan, Jr., Reg. No. 30,499; Ira J. Levy, Reg. No. 33,587; and Joseph R. Robinson, Reg. No. 33,448, all members of the bar of one or more states, all of the law firm of Darby & Darby, P.C., 707 Wilshire Blvd., 32nd Floor, Los Angeles, California 90017 and 805 Third Avenue, New York, New York 10022, as my attorneys and agents to prosecute this application and transact all business in the United States Patent and Trademark Office in connection therewith.

Please send all correspondence to:

Byard G. Nilsson
DARBY & DARBY, P.C.
707 Wilshire Blvd., 32nd Floor
Los Angeles, California 90017
Telephone (213) 243-8000

Date: May 25, 1999

By: Robert S. Deland
Robert S. Deland
4622 Bindewald Road
Torrance, California 90505

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)
Approved for use through 9/30/00. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63)	Attorney Docket Number	9127-0E006US1
	First Named Inventor	Robert S. Deland
	COMPLETE IF KNOWN	
	Application Number	/
	Filing Date	June 3, 1999
	Group Art Unit	not assigned
<input checked="" type="checkbox"/> Declaration Submitted with Initial Filing	OR	<input type="checkbox"/> Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)
Examiner Name		not assigned

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

MAG-STRIPE AUTHENTICATION AND VERIFICATION SYSTEM

the specification of which (Title of the Invention)

☒ is attached hereto

OR

☐ was filed on (MM/DD/YYYY) [] as United States Application Number or PCT International Application Number [] and was amended on (MM/DD/YYYY) [] (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
NONE			<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)
NONE	

☐ Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

[Page 1 of 2]

Burden Hour Statement This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)
Approved for use through 9/30/00. OMB 0651-0032

Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION — Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)
09/120,816	July 22, 1998	

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

☐ Customer Number

OR

☒ Registered practitioner(s) name/registration number listed below

Place Customer
Number Bar Code
Label here

Name	Registration Number	Name	Registration Number
Byard G. Nilsson	17,350		

☐ Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto.

Direct all correspondence to: ☐ Customer Number or Bar Code Label ☒ Correspondence address below

Name	Byard G. Nilsson		
Address	DARBY & DARBY, P.C.		
Address	707 Wilshire Boulevard, 32nd Floor		
City	Los Angeles	State	CA
		ZIP	90017
Country		Telephone	(213) 243-8000
		Fax	(213) 243-8050

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor: ☐ A petition has been filed for this unsigned inventor

Given Name (first and middle (if any))	Family Name or Surname
Robert S.	Deland

Inventor's Signature	<i>Robert S. Deland</i>	Date	5/26/99
Residence: City	Torrance	State	CA
		Country	U.S.A.
		Citizenship	USA

Post Office Address	4622 Bindewald Road		
Post Office Address			
City	Torrance	State	CA
		ZIP	90505
		Country	U.S.A.

☐ Additional inventors are being named on the _____ supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto